



# POS TS-201

## *Application Benefits :*

**Slim & Stylish Look**

**Improved reliability**

**Service & Upgrade with ease**

**Fits Various retail & hospitality environments**



# PROFICÓPIA

CONFIANÇA NA QUALIDADE



Black



White



# TS-201

**15" Ultra Wide LCD  
and Back light**

**True-Flat PCAP Touch**

**High speed Intel  
Processor**

**Fanless and Silent  
heat solution**

**Easy Swap HDD  
Lack type**

**Structure for easy  
maintenance**

**MSR/iButton for  
Identification**

**2nd Display and  
Customer Display**

## Specification

<b>Processor</b>	Intel® Celeron® J3455 (Apollo Lake)	Intel Core i3/i5/i7 (Kaby Lake)
<b>Memory</b>	DDR3L Standard 4GB (up to 8GB) Socket 1 x SODIMM	DDR4L Standard 4GB (up to 8GB) Socket 1 x SODIMM
<b>HDD</b>	2.5" SSD 128GB (up to 512GB)	
<b>LCD</b>	15.1" TFT LCD(Wide view) 1024*768 LED Backlight, 350 cd/m <sup>2</sup> (typ.)	
<b>Touch</b>	10 Point Capacitive Touch, USB interface Full-window type	
<b>OS</b>	Windows 10 IoT / Linux	
<b>Rear IO</b>	1x DC-12V 4-pin Power Input Connector 1x VGA Port with Power out(12V) 1x Ethernet Port (Gigabit RJ45) 2x USB (2.0) Serial port - COM1~2 (D-SUB 9Pin 5V/12V by BIOS) COM3~4 ( RJ45 with flow control, 5V/12V by BIOS ) COM5 ( RJ45 only RX/TX with 5V, Reserved for MSR with USB ) 1x Audio Jack (Line-out)	
<b>Back IO</b>	4x USB (2.0) RJ11 For CR Port (Virtual Com port)	
<b>Sound</b>	1 x 0.8W (Mono), *option 2 x 0.8W (Stereo)	
<b>Option</b>	2nd Display : 9.7" TFT LCD (1024 x 768), RGB Interface, Optional Touchscreen VFD, 20 Columns x 2 Lines Identification Reader (3 Track-HID & i-Button) by USB	
<b>Dimension</b>	364mm(W) * 340mm(H) * 210mm(D)	
<b>Certification</b>	FCC, CE, KC	
<b>Color</b>	White, Black	
<b>Power</b>	60W Adaptor Input 100~240V/50~60Hz, Output DC 12V/5A	

## Accessory (Option)



Dual Monitor



Customer Display



Identification Reader

## Port

